



## Europäisches Patentamt

**European Patent Office**

## Office européen des brevets



(11)

**EP 1 057 784 A1**

(12)

**EUROPEAN PATENT APPLICATION**

(21) Application number: 00201924.8

(22) Date of filing: 30.05.2000

(51) Int Cl.7: **C02F 1/00**, C02F 1/72,  
C02F 1/76  
// C02F103:44

(30) Priority: 02.06.1999 NL 1012217

(71) Applicant: **Appel, Peter Willem**  
**3062 DG Rotterdam (NL)**


(72) Inventor: Appel, Peter Willem  
3062 DG Rotterdam (NL)

(74) Representative: **Prins, Adrianus Willem et al**  
**Vereenigde,**  
**Nieuwe Parklaan 97**  
**2587 BN Den Haag (NL)**

(54) **Water purificaion plant**

(57) A water purification plant for a swimming pool (1) is provided with a filtering apparatus having a filtering circuit in which a filter (4) and a pump (3) are incorporated and via which water from the swimming pool can be circulated. In a further circuit arranged parallel to at

least a part of the filtering circuit, a UV reactor (8) is incorporated. Further, supply members (9) for an oxidizing and disinfecting agent are present. The oxidant in the UV reactor is introduced into the water flowing through said reactor.



## Description

[0001] The present invention relates to a water purification plant for a swimming pool, provided with a filtering apparatus having a filtering circuit in which a filter and a pump are incorporated and via which water from the swimming pool can be circulated, and with a further circuit which is arranged parallel to at least a part of the filtering circuit and in which a UV reactor is incorporated, and with supply members for an oxidizing and disinfecting agent. The further circuit can be arranged parallel to the entire filtering circuit as well as to only a portion thereof, while the parallel circuit can further terminate in the filtering circuit itself as well as in its own connection to the swimming pool.

[0002] Such water purification plants are known. Typically, chlorine or chlorine compounds are added to the water in the swimming pool. Apart from acting as disinfectant, chlorine has an oxidizing action. It reacts both to humic acids in the make-up water, involving the formation of chlorinated organic hydrocarbons, and to organic components such as urea, creatinine and the like, introduced into the water by swimmers, involving the formation of chloramines. For that reason, apart from the amount of chlorine required for disinfecting, an additional amount of chlorine usually has to be added to compensate for the oxidizing or chlorinating action of the chlorine. In order to limit the addition of chlorine, because of the undesired formation of chlorinated organic hydrocarbons and chloramines, it has earlier been proposed to have the oxidation take place by means of ozone. Since this is a toxic gas whose remainders still have to be removed separately, the use thereof causes great problems in practice. Moreover, in that case, chlorine for disinfecting the pool water has to be added nevertheless.

[0003] Further, there is known a purification of pool water where the UV reactor is not incorporated in a separate parallel circuit, but in the filtering circuit, while, also, the organic components are oxidized by means of hydrogen peroxide, while disinfection is effected by means of the UV reactor. Although at high concentrations, hydrogen peroxide may serve as oxidizing and disinfecting agent, and a UV reactor would even be superfluous, such high concentrations in the swimming pool water are highly undesirable, in particular for swimmers. However, at low concentrations, insufficient oxidation as well as insufficient disinfection takes place. A possible solution could be provided by causing the residence time of the circulating water in a hydrogen peroxide reactor incorporated in the filtering circuit to be very long and causing the residence time in the swimming pool to be very short. However, this meets with practical drawbacks, since such hydrogen peroxide reactor would have to be particularly large, which would involve unacceptably high costs.

[0004] The use of the combination of a UV reactor and ozone as oxidant in a water purification plant as de-

scribed in the preamble is also known per se. In that case, air is fed into the UV reactor, from which, under the influence of the UV radiation, ozone is obtained in situ; the ozonized air is passed through the water flowing through the UV reactor. However, the oxidizing action hereof proves to be very slight.

[0005] The object of the invention is to remove the above-mentioned drawbacks, or at least to reduce them to a considerable extent, and to provide a water purification plant wherein, in an efficient manner, both an oxidation of organic compounds introduced into the water and a sufficient disinfection of the water is obtained, while this no longer requires the addition of chlorine or other undesired substances in high concentrations, although this may in fact be desired sometimes, in particular in the case of an insufficient disinfection.

[0006] To realize this object, in a first embodiment, the water purification plant as described in the preamble is characterized in that the oxidant in the UV reactor is introduced into the water flowing through this reactor.

[0007] In a second embodiment, relating to a water purification plant for a swimming pool, provided with a filtering apparatus having a filtering circuit in which a filter and a pump are incorporated and via which water from the swimming pool can be circulated, this object is realized in that in the filtering circuit, a UV reactor is incorporated, while further, supply members for an oxidizing and disinfecting agent are present, the oxidant in the UV reactor being introduced into the water flowing through said reactor, and supply members for an additional disinfectant, such as chlorine, all types of chlorine compounds and silver salts, etc.

[0008] The oxidant is introduced into the UV reactor into the water flowing through this reactor. This can take place in the UV reactor itself, but also in the further circuit therefor, i.e. after the division in the filtering circuit. This may involve the addition of an excess of oxidant to the water; indeed, because the water, after having passed through the further conduit, is mixed with the water from the filtering circuit, while the oxidant concentration can be substantially reduced by dilution, swimmers will yet not be troubled by the added oxidant. Preferably, an oxidant is used whose oxidizing action is promoted under the influence of UV radiation.

[0009] Further advantages of the water purification plant according to the invention reside in the fact that the discharged water contains fewer chlorinated compounds, which renders the various organic compounds more readily biodegradable, while, further, less make-up water needs to be added. These advantages mean a lesser burden to the environment.

[0010] Instead of passing in situ-formed ozone through the water, which yields a poor oxidation, a direct supply of an oxidant to the water is particularly favorable. In that respect, it is important that the oxidant be water-soluble, i.e. sufficiently soluble to effect an efficient oxidation.

[0011] In particular, on the outlet side of the filter, a

distribution element is present, via which a fraction  $(1-\alpha)$  of the pool water, wherein  $\alpha$  lies approximately in the interval of from 0.03 to 0.5, more in particular from 0.05 to 0.2, and is preferably about 0.1, is directly returned over the filter conduit to the swimming pool and the rest of the pool water is returned to the swimming pool over the further circuit with the UV reactor. By subjecting, for instance, only 0.1 of the amount of circulated water to a direct oxidation, a very high concentration of oxidant can be introduced into the further circuit. After that, a dilution with 0.9 part of the circulated water takes place.

**[0012]** Further, it is particularly favorable when in the further circuit, on the inlet side of the UV reactor, make-up water is introduced. Indeed, when make-up water has to be added, as is necessary in practice, this will preferably take place where the high concentration of oxidant is added, because of the humic acids present in the make-up water.

**[0013]** As stated, through the features according to the invention, high concentrations of oxidant can be used without swimmers in the pool being troubled thereby. The concentration of active oxygen equivalents of the added oxidant will then be higher than the concentration of active oxygen equivalents of oxidizable organic compounds which is averagely introduced into the pool water by make-up water and by swimmers. In this respect, it is favorable when the concentration of active oxygen equivalents of the added oxidant (which can, for instance, be determined by means of potassium permanganate) is higher by a factor 2 to 100 and in particular 2 to 20, than the concentration of active oxygen equivalents of oxidizable organic compounds which is averagely introduced into the pool water by make-up water and by swimmers. In this manner, due to the high concentration of the oxidant in the second filtering circuit, an optimal oxidation of the oxidizable organic compounds introduced into the pool water is obtained, while this process proceeds considerably faster than in the case where the UV reactor were included in the first filtering circuit and the oxidant were injected therein. Further, in connection with the set UV radiation intensity, a disinfection (bacteriological equilibrium situation) can be realized.

**[0014]** Preferably, the oxidizing and disinfecting agent is formed by a peroxide compound, in particular hydrogen peroxide. Moreover, additionally, to meet any legal requirements concerning a prescribed degree of disinfection, a disinfectant, such as chlorine, all types of chlorine compounds and silver salts, etc., can further be added via means present for that purpose.

**[0015]** The invention will be specified with reference to the accompanying Figure, which schematically shows the water purification plant according to the invention.

**[0016]** The Figure shows a swimming pool 1 having a filtering circuit 2 incorporating a pump 3 and a filter 4. Arranged parallel to a part of this filtering circuit 2, via distributing elements 5 and 6, is a further circuit 7, which

circuit 7 incorporates a UV reactor 8 and means 9 for the supply of make-up water over the conduit 10. The UV reactor 8 comprises an injector via which an oxidant, supplied over a conduit 11, is introduced into the water flowing through the UV reactor. As oxidant, hydrogen peroxide is opted for. Further, the arrow 12 indicates the conduit via which an additional amount of a disinfectant can be added to the swimming pool water.

#### Example:

**[0017]** It is assumed that via the distributing element, 0.1 part of the circulated amount of water is passed through the circuit 7 and 0.9 part hereof is passed through the filtering circuit 2.


**[0018]** When it is assumed that averagely, per swimmer, about 2 m<sup>3</sup> should be circulated over a day of 8 hours, and that per day, 500 swimmers use the swimming pool, the total water circulation flow rate is 125 m<sup>3</sup>/hour, so that the flow rate of the water flowing through the circuit 7 is 12.5 m<sup>3</sup>/hour and that of the water that is directly returned to the pool is 112.5 m<sup>3</sup>/hour.

**[0019]** If it is further assumed that averagely, not considering the supply of make-up water, about 0.2 g of active oxygen equivalents of oxidizable organic compounds is introduced into the water per swimmer over a day of 8 hours, this is about 12.5 g/hour for 500 swimmers per day. This means that in the UV reactor, at least 1 g/m<sup>3</sup> of oxidizable organic compounds has to be oxidized in order to keep the concentration thereof in the pool constant. Through the addition of an excess of hydrogen peroxide at the inlet of the UV reactor, for instance 10-20 g/hour, there is realized at the inlet of the UV reactor a hydrogen peroxide concentration of 10-20 g/m<sup>3</sup> or 10-20 mg/liter - assuming that no notable decomposition of hydrogen peroxide takes place in the further circuit and the pool - and a virtually optimal oxidation of the oxidizable organic compounds introduced into the water by the swimmers proves to be possible in about 0.5 hour, while the concentration of the hydrogen peroxide in the swimming pool is sufficiently low for the swimmers not to be troubled thereby. To achieve a disinfecting situation under these conditions, apart from the amount of hydrogen peroxide required for optimal oxidation of said organic compounds, a relatively slight amount of chlorine should be added. Typically, this is even prescribed by law. Upon decomposition of hydrogen peroxide in the further circuit and in the pool, a compensation should be provided therefor in the dosing of the hydrogen peroxide.

**[0020]** The invention is in no way limited to the embodiment represented hereinabove, which shows the water purification plant only schematically, and not to the exemplary embodiment here described. The invention comprises all possible modifications hereof, of course in so far as they fall within the protective scope of the following claims.

## Claims

1. A water purification plant for a swimming pool, provided with a filtering apparatus having a filtering circuit in which a filter and a pump are incorporated and via which water from the swimming pool can be circulated, and with a further circuit which is arranged parallel to at least a part of the filtering circuit and in which a UV reactor is incorporated, and with supply members for an oxidizing and disinfecting agent, characterized in that the oxidant in the UV reactor is introduced into the water flowing through said reactor. 5
2. A water purification plant for a swimming pool, provided with a filtering apparatus having a filtering circuit in which a filter and a pump are incorporated and via which water from the swimming pool can be circulated, characterized in that in the filtering circuit, a UV reactor is incorporated, while further, supply members for an oxidizing and disinfecting agent are present, the oxidant in the UV reactor being introduced into the water flowing through said reactor, and supply members for an additional disinfectant, such as chlorine, all types of chlorine compounds and silver salts, etc. 10 15 20 25
3. A water purification plant according to claim 1 or 2, characterized in that the oxidant is water-soluble. 30
4. A water purification plant according to any one of the preceding claims, characterized in that on the outlet side of the filter, a distribution element is present, via which a fraction  $(1-\alpha)$  of the pool water, wherein  $\alpha$  lies approximately in the interval of from 0.03 to 0.5, more in particular from 0.05 to 0.2, and is preferably about 0.1, is directly returned over the filter conduit to the swimming pool and the rest of the pool water is returned to the swimming pool over the further circuit with the UV reactor. 35 40
5. A water purification plant according to any one of the preceding claims, characterized in that in the further circuit, on the inlet side of the UV reactor, make-up water is introduced. 45
6. A water purification plant according to any one of the preceding claims, characterized in that the concentration of active oxygen equivalents of the added oxidant is higher than the concentration of active oxygen equivalents of oxidizable organic compounds which is averagely introduced into the pool water by make-up water and by swimmers. 50
7. A water purification plant according to claim 6, characterized in that the concentration of active oxygen equivalents of the added oxidant is higher by a factor 2 to 100 and in particular 2 to 20, than the concentration of active oxygen equivalents of oxidizable organic compounds which is averagely introduced into the pool water by make-up water and by swimmers. 55
8. A water purification plant according to any one of the preceding claims, characterized in that the oxidizing and disinfecting agent is formed by a peroxide compound, in particular hydrogen peroxide.
9. A water purification plant according to any one of the preceding claims, characterized in that additionally, a disinfectant, such as chlorine, all types of chlorine compounds and silver salts, etc., can be added via means present for that purpose.





European Patent  
Office

## EUROPEAN SEARCH REPORT

Application Number  
EP 00 20 1924

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.7)
X	FR 2 726 309 A (PORTE PHILIPPE) 3 May 1996 (1996-05-03)	1,3,8	C02F1/00 C02F1/72 C02F1/76 //C02F103:44
Y	* page 1, line 26-30; claims; figures *	2,9	
Y	EP 0 027 278 A (SCHENCK GUENTHER O) 22 April 1981 (1981-04-22) * page 7 - page 10; claims; figure *	2,9	
A	US 5 424 032 A (CHRISTENSEN RONALD J ET AL) 13 June 1995 (1995-06-13) * claims *	1-9	
A	DE 94 15 140 U (ETC ENGINEERING & TECHNOLOGY C) 3 November 1994 (1994-11-03) * the whole document *	1-3,5-9	
A	US 5 190 659 A (WANG LAWRENCE K ET AL) 2 March 1993 (1993-03-02) * the whole document *	1-9	
A	EP 0 572 975 A (U V T SUD S R L ULTRAVIOLET TE) 8 December 1993 (1993-12-08) * claims 1-3 *	1,3,6-8	TECHNICAL FIELDS SEARCHED (Int.Cl.7) C02F
A	DATABASE WPI Week 9913 Derwent Publications Ltd., London, GB; AN 1990-097109 XP002129977 "Cleaning water in swimming pool - by treating with hydrogen peroxide and UV light" & SE 8 802 180 A (EKA NOBEL AB), 11 December 1989 (1989-12-11) * abstract *	1,3,6-8	
The present search report has been drawn up for all claims			
Place of search THE HAGUE		Date of completion of the search 19 September 2000	Examiner Gruber, M
<p>CATEGORY OF CITED DOCUMENTS</p> <p>X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document</p> <p>T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons &amp; : member of the same patent family, corresponding document</p>			

EPO FORM 1503 03/82 (PdC01)

ANNEX TO THE EUROPEAN SEARCH REPORT  
ON EUROPEAN PATENT APPLICATION NO.

EP 00 20 1924

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report. The members are as contained in the European Patent Office EDP file on  
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

19-09-2000

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
FR 2726309 A	03-05-1996	NONE	
EP 0027278 A	22-04-1981	DE 2941742 A	14-05-1981
US 5424032 A	13-06-1995	AT 153319 T	15-06-1997
		BR 9306779 A	08-12-1998
		CA 2139934 A	03-02-1994
		WO 9402423 A	03-02-1994
		DE 69310912 D	26-06-1997
		DE 69310912 T	16-10-1997
		DE 651730 T	14-03-1996
		EP 0651730 A	10-05-1995
		ES 2076133 T	01-11-1995
DE 9415140 U	03-11-1994	NONE	
US 5190659 A	02-03-1993	US 5236595 A	17-08-1993
EP 0572975 A	08-12-1993	IT 1257212 B	10-01-1996
SE 8802180 A	11-12-1989	NONE	

EPO FORM P449

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82